


Download



601 Disanlens LED

New developments were also introduced in some of the best sellers of Disano's interior lighting range. The new Disanlens ceiling lamp represents the ideal solution for the relamping of spaces where optimal light distribution is key for ensuring maximum visual comfort. Thanks to its original design, specifically studied to be inserted into large commercial spaces or in offices and school buildings, Disanlens is the best solution for excellent light distribution.

LED sources allow savings that reach 30% compared to traditional T5 and even 60% compared to the T8 lamps.

With a life of 50000 hours, Disanlens meets the needs of systems that require long ON times.

With the new Disanlens, schools, offices and healthcare facilities can update their lighting systems, saving energy with higher light quality. The ceiling lamp features the best technologies and latest generation LED sources

Housing: in extruded aluminium with closing ends. Diffuser: in shatter-proof, self-extinguishing and UV-stabilised V2 polycarbonate. Smooth and dust-proof on the outside, and multiple grooves on the inside to increase light distribution.

Coating: smooth, white powder coating. Equipment: silicone rubber gasket; outer screws in stainless steel. IP44 LED:

L = 520mm - 13W tot - 2400lm - 4000K - CRI>80

L = 1000mm - 27W tot - 4800lm - 4000K - CRI>80

L = 1480mm - 43W tot - 6800lm - 4000K - CRI>80

Power factor 0.9. Luminous flux maintenance 70%: 50.000h (L70B20).

Photobiological safety class: Exempt group.

Code	Gear	Kg	Watt	Base	Lamps	Colour
115594-00	CLD CELL	1.49	LED white 13W		2400lm-4000K-CRI 80	WHITE
115595-00	CLD CELL	2.71	LED white 25W		4800lm-4000K-CRI 80	WHITE
115596-00	CLD CELL	3.89	LED white 40W		6800lm-4000K-CRI 80	WHITE
115594-12	CLD CELL-D	2.71	LED white 13W		2400lm-4000K-CRI 80	WHITE
115595-12	CLD CELL-D	3.71	LED white 25W		4800lm-4000K-CRI 80	WHITE
115596-12	CLD CELL-D	4.71	LED white 40W		6800lm-4000K-CRI 80	WHITE
115594-19	CLD CELL	2.71	LED white 13W		2400lm-4000K-CRI 80	WHITE
115595-19	CLD CELL	3.71	LED white 25W		4800lm-4000K-CRI 80	WHITE
115596-19	CLD CELL	4.71	LED white 40W		6800lm-4000K-CRI 80	WHITE
115594-07	CLD CELL-E	1.99	LED white 13W		2400lm-4000K-CRI 80	WHITE
115595-07	CLD CELL-E	3.29	LED white 25W		4800lm-4000K-CRI 80	WHITE
115596-07	CLD CELL-E	3.89	LED white 40W		6800lm-4000K-CRI 80	WHITE

Accessori



- 588 bracket